



# CARNOTJET™ SYSTEM PRODUCT SPECIFICATIONS AND DATA



RACK(S)

	13U Evaluation Unit	42U System	4 x 42U System
RACK CAPACITY	Up to 6 kW	5 kW - 100 kW	4 x 5 kW - 100 kW
RACK DIMENSIONS	26 in x 30 in x 51 in	6 ft x 26 in x 52 in	10 ft x 15 ft x 52 in
RACK SQUARE FOOTAGE	~4.5 sq ft	13 sq ft	150 sq ft
COOLANT REQUIRED	85 gallons	255 gallons	1020 gallons
RACK WEIGHT (WITHOUT COOLANT)	150 lbs	300 lbs	1,200 lbs
RACK WEIGHT (WITH COOLANT)	675 lbs	2,085 lbs	8,340 lbs
RACK WEIGHT (FULLY LOADED)	~1,065 lbs	~3,380 lbs	~13,520 lbs
SECONDARY CONTAINMENT	Modular	Modular	Perimeter berm
LID	Brushed aluminum	Brushed aluminum	Brushed aluminum
FINISH	White powder coat	White powder coat	White powder coat

PUMP MODULE

PUMP MODULE DIMENSIONS	31 in x 50 in x 29.25 in	34 in x 55 in x 57 in	34 in x 55 in x 57 in
PUMP MODULE CAPACITY	One 6 kW Rack	1 Rack (Expandable)	1-4 Racks
HEAT EXCHANGERS	Single	1-2	3-4
PUMP WEIGHT	~300 lbs	~650 lbs	~800 lbs
POWER TYPE	110v/208v	110v/208v	110v/208v
MAX POWER DRAW	<5% of compute	<5% of compute	<5% of compute
RADIATOR	Yes	No	No