



## Micro-Modular, Rack-Based Cooling Solutions for Blockchain Computing. Simple. Efficient. Limitless.

### Product Specifications

Number of Immersion-Cooled Racks	1 or 2 52U Racks
Cooling Capacity	Cooling Capacity (per CDU) 200 kW Chiller-Free Water @ 32° C (89.6°F)
Power Requirements	5.6 kW (max)
Rack Dimensions-Approximate	100" x 27" x 52" (2.54 m x 0.7 m x 1.3 m)

### Power & Water Specifications

Final Heat Rejection Type (not included) <sup>1</sup>	Evaporative Cooling Tower
Water Requirements	Possible water input temperature 5 to 32°C (41 to 89.6°F)  Recirculating water flow rate 21 to 30 m <sup>3</sup> /hr (50 to 150 gpm)  Connections 50.8 mm (2.0") FNPT or hose barb
Input Voltage (Primary and secondary feeds, each with these characteristics)	CDU: 3-phase 200 to 240 VAC or 380 to 480 VAC, 50 to 60 Hz

### Delivery & Installation

Shipping Lead Time	• 12 to 14 weeks after receipt of purchase order
Shipping Terms	• Ex Works
Installation	• Three days for the first unit, plus two days for each subsequent unit. GRC service engineer(s) will be onsite to perform installation and training.

For More Information and Pricing Contact Us

**+1.512.692.8003 • [ContactUs@grcooling.com](mailto:ContactUs@grcooling.com) • [grcooling.com](http://grcooling.com)**

<sup>1</sup> Low water use options available in climates where the design dry bulb temperature does not exceed 90°F/35°C. Additional costs apply.



### Site Preparation

#### Customer to Provide

- Mining hardware
- Installation preparation, including electrical & plumbing design and construction
- Cooling towers, including water treatment and plumbing to CDUs
- Electrical distribution with appropriate breakers and panels
- Applicable permits
- Firewall/routers/switches
- Internet connection for miners
- Bitcoin wallet and mining pool account

### Representative Terms

#### Payment Terms

- 80% with purchase order
- 20% before shipment
- Terms are subject to credit approval

#### Warranty & Maintenance<sup>2</sup>

- One-year limited warranty with customized support options available.

<sup>2</sup>Warranty is void if the HashRaQ units are run outside of their operating parameters defined in the installation specification.

GRC believes the information in this Data Sheet to be accurate; however, GRC does not make any representation or warranty, express or implied, as to the accuracy or completeness of any such information and shall have no liability for the consequences of the use of such information.

This Data Sheet and its contents do not constitute an order by GRC to sell any product. An order is made only by a quotation provided by GRC. The terms of sale in such quotation may vary from those set forth in this Data Sheet. GRC's acceptance of any order shall be in GRC's sole discretion, and all quotations and sales are subject to GRC's Terms and Conditions of Commercial Sale.